

Heated & Refrigerated Key Features

Designed for safely transporting food from a kitchen to a serving/ banqueting area



01. All round non-marking bumper for added protection during transfer of cabinet
02. Built-in handles at four sides for easy mobility
03. Excellent thermal efficiency, high density 75mm thick polyurethane insulation with Zero ODP (Ozone Depletion Potential) and Low GWP (Global Warming Potential)
04. Removable anti-tilt trayslides to prevent tipping
05. Self-closing doors minimise cool air loss and reduce energy consumption
06. Over 90° door opening allows easy loading and stock checking
07. 155Hmm heavy duty, non-marking swivel and braked castors for easy positioning
08. CoolSmart controller with clear digital display is designed for easy operation
09. Fitted with circulation fans to ensure even temperature and fast warm-up throughout the cabinet *
10. Equipped with manual re-set safety cut-out switch to prevent overheating *
11. Anti-condensation door mullion heaters #
12. Removable balloon type magnetic door gasket with air release points provides an excellent seal to prevent heat ingress, easy replacement and avoiding dirt traps #
13. Forced air refrigeration system ensures effective air circulation #
14. Imported, durable and energy-efficient compressor #
15. Evaporator with Cataphoresis plated coils provides high corrosion resistance properties #
16. Accurate helium leak detection system ensures the quality of the entire refrigeration system #
17. Automatic defrost ensures the evaporator working to its optimum performance #
18. Automatically vaporises defrost water, drainage is not required #
19. Designed and engineered to operate up to 43°C ambient #
20. Environmental-friendly CFC-free refrigerant (R134a) #
21. HACCP compliant

* Available for MHC only

Available for MRC only

Heated & Refrigerated

Specification

- Accommodates 2/1 GN size
- Foodsafe 304 grade stainless steel exterior (including back and base) and interior
- Fitted with cylindrical lock

Options

1. Freezer type *
2. 220V / 60HZ / 1PH

* Available for MRC only



Heated & Refrigerated Technical Data

Model	MHC10SS	MHC16SS	MHC32SS	MRC10SS	MRC16SS	MRC32SS
Temp Range (°C)	+78 / +82	+78 / +82	+78 / +82	+1 / +4	+1 / +4	+1 / +4
External Dimension (mm)						
Width	807		1470	807		1470
Depth	885					
Height	1371	1768		1603	2000	
Internal Dimension (mm)						
Width	590		1250	590		1250
Depth	650					
Height	918	1315		833	1230	
Thickness of 304 grade stainless steel (mm)						
Exterior	0.7					
Interior	0.6					
Door	0.8					
Opening Depth (mm)						
1480						
Capacity (cu.ft / litres)						
	13.8 / 391	19.4 / 550	41.3 / 1172	13.5 / 384	19.2 / 544	40.9 / 1159
Power Supply						
220V / 50HZ / 1PH						
	13 amp plug		32 amp 3p IP67 plug	13 amp plug		
Power Input - Running (amps)						
	6	13	18	2.4	3	3.5
Rating Power (watts) *						
	1320	2860	3960	528	660	770
Compressor (HP)						
	N/A			1/4	1/3	
Heat Rejection (watts) (Evaporating at -10°C in 32°C ambient)						
	N/A			485	623	
Refrigerant						
	N/A			R134a		
Standard fittings						
Trayslides (pair)	10	16	32	10	16	32

* 20% increase for 60HZ power supply

v3