Varitemp Drawer Key Features

Adjustable Chill-freeze temperature range and effective drawer design with durable worktop provide the greatest flexibility with its small footprint



- ○1. Chill-freeze storage temperature range covered -22°C to +4°C and can be easily adjusted to be a chiller or freezer
- Special cooling system configuration maintains the small footprint especially for compact kitchen design
- O3. Designed for serving as undercounter units or counter units with tough, durable and heat resistant worktop
- Easy servicing condensing unit and evaporator
- 5. Fully extendable work out drawer fitted as standard for easy accessing and better organising the food products
- O6. Excellent thermal efficiency, high density polyurethane insulation with Zero ODP (Ozone Depletion Potential) and Low GWP (Global Warming Potential)
- 7. Anti-condensation drawer mullion heaters
- Removable balloon type magnetic drawer gasket with air release points provides an excellent seal to prevent heat ingress, easy replacement and avoiding dirt traps
- 75Hmm heavy duty, non-marking swivel and braked castors for easy positioning (50Hmm for stacking model)

- 1 O. Forced air refrigeration system ensures effective air circulation from the top
- Clear digital display is designed for easy operation, it also features with built-in alert and fail safe run facility
- 12. Imported, durable and energy-efficient compressor
- 13. Condenser and evaporator with Hydrophilic aluminium fins provides high corrosion resistance properties
- 14. Accurate helium leak detection system ensures the quality of the entire refrigeration system
- 15. Automatic defrost ensures the evaporator working to its optimum performance
- 16. Automatically vaporises defrost water, drainage is not required
- Designed and engineered to operate up to 43°C ambient
- 18. Environmental-friendly CFC-free refrigerant (R134a)
- 19 HACCP compliant

Note: Products are NOT designed for outdoor application, please contact Williams team for any special requirement.



Varitemp Drawer

Specification

- Accommodates 2/1 GN size
- Foodsafe 304 grade stainless steel exterior and interior
- 1.2mm thick durable 304 grade stainless steel table top
- Galvanised steel exterior back and base
- Fitted with cylindrical lock

Options

- 1. 304 grade stainless steel exterior back / base
- 2. Right-hand-side condensing unit
- 3. Adjustable legs in lieu of castors
- 4. 220V / 60HZ / 1PH

Product List



Varitemp Drawer Technical Data

| Model | UBC-VT-21-1(150H) | UBC-VT-21-2(150H) | UBC-VT-21-1(200H) |
|---|-------------------|-------------------------|-------------------|
| Temp Range (°C) | -22 / +4 | -22 / +4 | -22 / +4 |
| External Dimension (mm) | | | |
| Width | 1090 | | |
| Depth | 670 | 670 + 50 (rear bracket) | 670 |
| Height (include castors) | 470 | 840 | 520 |
| Opening Depth (mm) | 1275 | | |
| Capacity (cu.ft / litres) | 1 (150Hmm) | 2 (150Hmm) | 1 (200Hmm) |
| Power Supply | 220V / 50HZ / 1PH | | |
| | 13 amp plug | 13 amp plug x 2 | 13 amp plug |
| Power Input - Running (amps) * | 4.5 | 4.5 x 2 | 4.5 |
| Rating Power (watts) * | 990 | 990 x 2 | 990 |
| Compressor (HP) | 1/6 | 1/6 x 2 | 1/6 |
| Heat Rejection (watts) (Evaporating at -10°C at 32°C ambient) | 826 | 826 x 2 | 826 |
| Refrigerant | R404a | | |

^{* 20%} increase for 60HZ power supply

